

WEBEL TECHNOLOGY LIMITED

CORRIGENDUM – I

TENDER NO. WTL/KP/CCTV/22-23/015 dated 26.07.2022

Sl.	Page	Section	Clause No.	Present Entry	Replace with
1	90	R		As Section I and Section R is similar. So Bidders are requested to fill only section I only.	
2	34	D	28	PERFORMANCE BANK GUARANTEE (PBG) As a guarantee for timely delivery, installation and commissioning of equipment as well as performance of on-site warranty support, as mentioned in Bill of Material, from the date of final acceptance of systems and pertaining to proper running of the systems, the bidder will have to submit 10 % of the contract value (Excluding TAX amount) as security in the form of Performance Bank Guarantee from any nationalized bank as per format enclosed (Section – O).	PERFORMANCE BANK GUARANTEE (PBG) As a guarantee for timely delivery, installation and commissioning of equipment as well as performance of on-site warranty support, as mentioned in Bill of Material, from the date of final acceptance of systems and pertaining to proper running of the systems, the bidder will have to submit 3 % of the contract value (Excluding TAX amount) as security in the form of Performance Bank Guarantee from any nationalized bank as per format enclosed (Section – O).
3	72	M	1	Smart Managed Switch having 24x 1G SFP slots with & 4x 10G SFP+ slots. IEEE 802.3 10BASE-T Ethernet, IEEE 802.3u 100BASE-TX Fast Ethernet, IEEE 802.3ab 1000BASE-T Gigabit Ethernet, 802.3ae 10 GbE, IEEE 802.3x Flow Control for Full- Duplex Mode, Auto-negotiation	Smart Managed Switch having 24x 1G Copper slot with & 2x 1G SFP, 2x 10G SFP+ slots IEEE 802.3 10BASE-T Ethernet, IEEE 802.3u 100BASE-TX Fast Ethernet, IEEE 802.3ab 1000BASE-T Gigabit Ethernet, 802.3ae 10 GbE, IEEE 802.3x Flow Control for Full- Duplex Mode, Auto-negotiation
4	20	B	54	Unit is “NOS”	Unit will be “Meter”
5	65	M	Revised IR ILLUMINATOR Specification mentioned below		

IR Illuminator

Sl. No	Feature	Technical Specification	Compliance (Yes/No)	If any deviation (Yes/No)
1	Light Type	12 PCS High Power IR LED or Better		
2	Wavelength	850nm or Better		
3	Beam Angle	45°/ 60°or Better		
4	Day and night switch	Auto		
5	IR Distance	Minimum 100 Meter		
6	Plug	AC110-220V (standard)		
7	Panel	Tempered glass		
8	Housing	Aluminum Die Casting Housing		
9	Working temperature	0°C~50°C or Better		
10	Rate	IP66		
11	Make / Brand	Any globally reputed Manufacturer presence in India.		